

**Spatial Evaluation of Potential Tsunami Vertical
Evacuation: A Case Study of the Western Coastal
Belt in Sri Lanka**

January 2019

Manjula Mahinda RANAGALAGE

**Spatial Evaluation of Potential Tsunami Vertical
Evacuation: A Case Study of the Western Coastal
Belt in Sri Lanka**

A Dissertation Submitted to
the Graduate School of Life and Environmental Sciences,
the University of Tsukuba
in Partial Fulfillment of the Requirements
for the Degree of Doctor of Philosophy in Science
(Doctoral Program in Geoenvironmental Sciences)

Manjula Mahinda RANAGALAGE

Abstract

On December 26, 2004, a massive earthquake occurred near the coast of Sumatra, Indonesia, and it was the worst tsunami incident ever recorded in the Indian Ocean. Fourteen countries were affected by this hazard, and four countries—Indonesia, India, Sri Lanka, and Thailand—were severely damaged. The recorded death toll was more than 35,000, and approximately one million people were affected in Sri Lanka. After this tsunami incident, Sri Lanka was also categorized as a tsunami-vulnerable country. Several past studies have contributed to introducing proper mechanisms that would minimize the damages from the next tsunami incident. Most tsunami-vulnerable areas have been covered by horizontal tsunami evacuation based on the elevation profile of the area. However, in Sri Lanka, people need to travel great distances to reach tsunami evacuation centers due to the lower elevation profile of the coastal area.

The purpose of this study was to spatially evaluate the potential for tsunami vertical evacuation in the western coastal belt in Sri Lanka. The Moratuwa Municipal Council Area (MMCA) was selected for this case study by considering the existing urban structure and the tsunami vulnerability of the western coastal belt. Several criteria and assumptions have been computed to achieve the goal of the study. A geographic information system (GIS), remote sensing (RS), and demographic data facilitated the completion of the following tasks: (i) preparation of three tsunami scenarios based on the 2004 tsunami experience; (ii) updating the building layer and calculating the building height and volume by using airborne light detection and ranging (LiDAR) data; (iii) calculating the inundation ratio building volume loss, available building volume, and nighttime population; (vi) identifying the tsunami vertical evacuation sites based on the existing urban spatial structure; (vii) estimating the maximum capacity of the selected vertical evacuation sites using a usable building volume index (UBVI) and volume

determination factor (VDF); and (vii) calculating tsunami arrival time, distance and time from resident place to evacuation centers in three tsunami scenarios.

The MMCA is located in the south direction of the Colombo district and is the fifth largest municipal council in Sri Lanka with a total population of 168,280 as of 2012. The MMCA has unique physical characteristics as it is a natural peninsula covered by complex water bodies such as the Indian Ocean, Bolgoda Lake, and Lunawa Lagoon. In 2004, the Indian Ocean tsunami affected both life and property in the MMCA. The development pattern of the MMCA will denote significant damages in the next tsunami disaster. Several tsunami horizontal evacuation centers have been identified inside the MMCA, but most of them are located away from the coastal belt. The residents need to travel long distances to reach a safe location, and it is a challenging task, especially in nighttime tsunami events. Thus, a nighttime tsunami incident was selected by considering current evacuation procedures and the tsunami vulnerability of the study area. Identifying potential vertical evacuation sites near residential areas will benefit the residents for effective tsunami evacuation. Hence, it is necessary to study the potential of vertical tsunami evacuation to provide more alternatives to evacuate during nighttime tsunami disasters.

In this analysis, three tsunami scenarios—4 m, 8 m, and 12 m—were used to identify potential vertical evacuation sites. According to the results of the inundation ratio, the category of critical buildings can be increased to 1.7% and 67.0% in 4 m and 12 m scenarios, respectively. It was indicated that the 12 m scenario consisted of more damage than the other two scenarios. Regarding the evacuation sites, 220, 232, and 122 were selected for the 4 m, 8 m, and 12 m scenarios, respectively.

VDF was used to calculate the UBVI of each building to demarcate the capacity of each selected site. The VDF was calculated based on expert knowledge and fieldwork by considering

the types of buildings, primary usage and building volume. According to the calculations of the capacity of each site, the selected 220 sites will facilitate 17,594 people during the 4 m tsunami scenario. The selected 232 sites will accommodate 25,677 people during the 8 m scenarios. All selected sites are capable of accommodating the affected population in both the 4 m and the 8 m scenarios. However, the selected evacuation sites are not sufficient for accommodating the affected population in the 12 m scenario. In the 12 m scenario, 12,221 people are affected. However, the evacuation sites can only accommodate 10,165 people.

The finding of vertical evacuation by considering the existing urban structure of the city is essential to save human lives during the next tsunami incident. The adopted methodology can be used as an example for other lowland coastal cities to select vertical evacuation to protect human life. The selected evacuation of the MMCA area provides vital information for a comprehensive tsunami evacuation plan in the future. In addition, the use of the UBVI and the VDF to calculate an accurate number of people who can be accommodated in the evacuation sites is important in the tsunami research field. Most previous researches used whole available building volume for capacity calculations. However, each building had been established based on a specific objective. The application of the VDF and the UBVI provides the real picture of the capacity of the evacuation sites. It can be used as a proxy indicator in future tsunami vertical evacuation calculations.

This study contributes to the use of existing urban structures to identify vertical evacuation sites based on three tsunami scenarios. The capacity estimation was done based on the newly proposed two indexes (UBVI and VDF), and this methodology can be used as a reference methodology in future tsunami vertical evacuation studies for different locations, especially lowland coastal cities to produce similar results. This study's approach combines several methods based on the GIS platform. The results can be used as proxy indicators for

policymakers and disaster planners to provide adequate evacuation plans in vulnerable coastal communities.

Keywords: tsunami scenario, DSM, DTM, building volume, VDF, UBVI, Moratuwa Municipal Council area, vertical evacuation, nighttime population, tsunami

Table of Contents

Abstract.....	i
Table of Contents	v
List of Figures.....	viii
List of Tables	xi
Abbreviations	xii
1. Chapter 1: Introduction	1
1.1. Background and problem statements	1
1.2. Literature review	3
1.2.1. Historical perspective of tsunami in the Indian Ocean	3
1.2.2. Tsunami effect in Sri Lanka.....	6
1.2.3. Tsunami vertical evacuation	11
1.3. Research objectives.....	22
1.4. Methodology	24
2. Chapter 2: Study area: The Moratuwa Municipal Council Area	27
2.1. The geographical setting.....	27
2.2. The urban structure of the MMCA	30
2.3. Demographic pattern.....	36
2.4. Socio-economic pattern	41
2.5. Current tsunami evacuation plan of Sri Lanka.....	41
2.6. Current disaster management plan in the MMCA	44

2.7. Data collection	49
3. Chapter 3: Spatial distribution of building volume and nighttime population in the MMCA	51
3.1. Introduction.....	51
3.2. Material and methods.....	51
3.2.1. Data collection	51
3.2.2. Methodology	53
3.3. DSM & DTM generation	55
3.4. DHM generation	58
3.5. Updating and separation of the existing building footprint	60
3.6. Building height and volume estimation	62
3.7. Estimation of nighttime building population	65
4. Chapter 4: The spatial pattern of tsunami inundation scenarios in the MMCA	77
4.1. Introduction.....	77
4.2. Calculation assumptions	77
4.3. Methodology	77
4.4. Tsunami inundation scenarios.....	79
4.5. Calculation of water depth.....	85
4.6. Calculation of the inundation ratios, affected buildings, and population.....	85
4.7. Building volume loss and available volume	96
5. Chapter 5: Distribution of tsunami vertical evacuation sites in the MMCA.....	110
5.1. Introduction.....	110
5.2. Current evacuation procedures in the MMCA.....	111

5.3. Criteria and assumptions.....	119
5.4. Criteria application and vertical evacuation analysis.....	121
5.5. The calculation of tsunami arrival time	132
5.6. Results.....	133
5.6.1 Tsunami vertical evacuation	133
5.6.2. Tsunami arrival time, evacuation distance, and time	141
5.7. Discussion.....	155
6. Chapter 6: Conclusions	168
Acknowledgments	172
Reference	174

List of Figures

Figure 1-1: Location of the tsunami triggers in the Indian Ocean.	5
Figure 1-2: Spatial distribution of tsunami wave height and inundation for the east coast of Sri Lanka.	8
Figure 1-3: Spatial distribution of tsunami wave height and inundation for the south coast of Sri Lanka.	9
Figure 1-4: Spatial distribution of tsunami wave height and inundation for the west coast of Sri Lanka.	10
Figure 1-5: Simple and economical vertical evacuation structure in Japan.	12
Figure 1-6: A concrete structure in Kaifu, Japan as a vertical evacuation site.	13
Figure 1-7: Vertical evacuation structure at Shirahama Beach Resort in Japan to protect people from the tsunami incident.	14
Figure 1-8: Methodology framework of the study.	26
Figure 2-1: Location of the Moratuwa Municipal Council area.	29
Figure 2-2: Spatial distribution of built-up area from 1997 to 2017.	31
Figure 2-3: Land use of study area based on the Orthophoto 2015.	32
Figure 2-4: Statistics of land use pattern of the study area 2015.	33
Figure 2-5: Spatial distribution of building based on the heights (m) in MMCA 2015.	35
Figure 2-6: The temporal variation of population.	37
Figure 2-7: Age structure of Moratuwa MC Area.	38
Figure 2-8: Examples of buildings structure of MMCA.	40
Figure 2-9: Tsunami evacuation order and structure in Sri Lanka.	43
Figure 2-10: Tsunami early warning tower located in the school to aware the people.	45
Figure 2-11: Tsunami early warning sirens located in the study area.	46
Figure 2-12: Current safety location of Moratuwa MCA.	48
Figure 3-1: Flowchart of the methodology.	54
Figure 3-2: DTM of the study area based on LiDAR.	56

Figure 3-3: DSM of the study area based on LiDAR.....	57
Figure 3-4: DHM of study area based on LiDAR.....	59
Figure 3-5: Building categories of the study area, 2015.	61
Figure 3-6: Building volume (m ³) of the study area in 2015.	63
Figure 3-7: Statistics of building volume (m ³) 2015.....	64
Figure 3-8: Graphical illustration of population estimation model.....	67
Figure 3-9: Population estimation model in the study area.....	69
Figure 3-10: Population of the study area by GN divisions 2012.....	73
Figure 3-11: Nighttime population estimation by buildings of the study area, 2012.....	75
Figure 3-12: Statistics of nighttime building population estimation by building volume.....	76
Figure 4-1: The simplified procedure of methodology.	78
Figure 4-2: 4m run-up tsunami inundation scenario in the MMCA.	81
Figure 4-3: 8m run-up tsunami inundation scenario in the MMCA.	82
Figure 4-4: 12m run-up tsunami inundation scenario in the MMCA.	83
Figure 4-5: Spatial distribution of the inundation ratio of buildings in the study area, 4m scenario.	90
Figure 4-6: Spatial distribution of the inundation ratio of buildings in the study area, 8m scenario.	91
Figure 4-7: Spatial distribution of the inundation ratio of buildings in the study area, 12m scenario.	92
Figure 4-8: Building volume loss due to 4m run-up tsunami.	98
Figure 4-9: Building volume loss due to 8m run-up tsunami.	99
Figure 4-10: Building volume loss due to 12m run-up tsunami.	100
Figure 4-11: Statistics of number of the building based on building volume loss 2015.....	102
Figure 4-12: Available building volume loss due to a 4m run-up tsunami.....	103
Figure 4-13: Available building volume loss due to an 8m run-up tsunami.....	104
Figure 4-14: Available building volume loss due to a 12m run-up tsunami.....	105
Figure 5-1: Method of getting a tsunami evacuation early warning.	112
Figure 5-2: Community satisfaction about the evacuation centers..	115
Figure 5-3: Community response regarding the locating vertical evacuation site near the residential area.....	116

Figure 5-4: Building usage of selected evacuation site in the 4m scenario.	126
Figure 5-5: Building usage of selected evacuation site in the 8m scenario.	127
Figure 5-6: Building usage of selected evacuation site in the 12m scenario.	128
Figure 5-7: UBVI of selected tsunami vertical evacuation sites in the 4m scenario.....	129
Figure 5-8: UBVI of selected tsunami vertical evacuation sites in the 8m scenario.....	130
Figure 5-9: UBVI of selected tsunami vertical evacuation sites in the 12m scenario.	131
Figure 5-10: Spatial distribution of the potential of vertical evacuation site and allocated population in the 4m scenario.	135
Figure 5-11: Spatial distribution of the potential of vertical evacuation site and allocated population in the 8m scenario.	137
Figure 5-12: Spatial distribution of the potential of vertical evacuation site and allocated population in the 12m scenario.	139
Figure 5-13: Tsunami arrival time in 4m scenario.....	143
Figure 5-14: Distance to resident place to tsunami vertical evacuation center in 4m scenarios....	144
Figure 5-15: Tsunami evacuation time from residence place to tsunami evacuation center – 4m.	145
Figure 5-16: Tsunami arrival time in 8m scenario.....	147
Figure 5-17: Tsunami evacuation time from residence place to tsunami evacuation center – 8m.	148
Figure 5-18: Tsunami evacuation time from residence place to evacuation center – 8m.	149
Figure 5-19: Tsunami arrival time in 12m scenario.....	151
Figure 5-20: Distance to resident place to tsunami vertical evacuation center in 12m scenarios. .	152
Figure 5-21: Tsunami evacuation time from residence place to tsunami evacuation center – 12m.	153
Figure 5-22: Vertical evacuation movement in 4m tsunami scenario.....	157
Figure 5-23: Vertical evacuation movement in 8m tsunami scenario.....	159
Figure 5-24: Vertical evacuation movement in 12m tsunami scenario.....	160
Figure 5-25: Tsunami arrival time in minutes after the earthquake for tsunamis generated: (a) Northern Sumatra-Andaman subduction Zone, (b) Southern Sumatra subduction Zone, (c) Arakan Subduction Zone, and (d) Makran Subduction Zone.....	165

List of Tables

Table 1-1: Component of vertical evacuation plan.	16
Table 2-1: Housing units by type of structure of Moratuwa MC Area.	39
Table 2-2: Tsunami safety location of Moratuwa MCA.	47
Table 2-3: List of the data layers used in this research.	50
Table 3-1: Data used to create building volume and nighttime building population estimation.	52
Table 3-2: Population of selected GN divisions in the study area based on the census of population and housing in 2012.	71
Table 4-1: Statistics of tsunami inundation scenario.	84
Table 4-2: Inundation ratio classification.	87
Table 4-3: Building affected by tsunami scenarios.	93
Table 4-4: Population affected by tsunami scenarios.	95
Table 4-5: Building volume loss calcification.	97
Table 4-6: Statistics of available building volume in three tsunami scenarios.	107
Table 4-7: Statistics of building volume loss and available volume.	109
Table 5-1: Preference of buildings as a vertical evacuation site.	118
Table 5-2: Criteria and assumption for vertical evacuation in 4, 8 and 12m scenarios.	120
Table 5-3: Details of calculating volume determination factor by considering building volume.	122
Table 5-4: Calculation of volume determination factor.	125
Table 5-5: Allocated population for selected vertical evacuation site in the 4m scenario.	136
Table 5-6: Allocated population for selected vertical evacuation site in the 8m scenario.	138
Table 5-7: Allocated population for selected vertical evacuation site in the 12m scenario.	140
Table 5-8: Statistics of tsunami arrival time and distribution of tsunami vertical evacuation sites.	154
Table 5-9: Distance from resident place to tsunami evacuation center.	163
Table 5-10: Tsunami evacuation time from residence place to tsunami evacuation center.	164

Abbreviations

MMCA	Moratuwa Municipal Council Area
CBD	Central Business District
GIS	Geographical Information Systems
RS	Remote Sensing
DSM	Digital Surface Model
DTM	Digital Terrain Model
DHM	Digital Height Model
VDF	Volume Determination Factor
UBVI	Usable Building Volume Index
MCDA	Multi-criteria Decision Analysis
UV	Urban Volume